

Pano 2-piece metal can · diameter 76 mm

For packaging of non-liquid food products · Composed of caps (D) and tin cans (UT)



Side view

Top view

Product description

D/UT and diameter/height + 8-digit Code:

- 1st digit = internal code (0)
- 2nd digit = button function (without = 0)
- 3rd digit = compound type (without = 0)
- 4th digit = interior priming
- 5th digit = interior adhesive lacquer
- 6th digit = exterior basecoat
- 7th digit = number of print colours
- 8th digit = exterior protective lacquer

Production program

| | | |
|------------------------------|--|-----------------|
| Cap Tin can | D 76/11 | UT 76/20 |
| Diameter max. [mm] | 76.29 | 76.41 |
| Height max. [mm] | 11.2 | 21 |
| Composition | | |
| Plate | Tin plate acc. EN 10202:2001, tin weight 2.0 g/m ² per side | |
| Interior system | 1-layer coating system, with sufficient corrosion protection for sweets | |
| Exterior system | 2-layer coating system (white, gold or clear), lid and body are non-sealable | |
| Printing | Acc. customer specifications | |
| Packaging | | |
| Weight | 10.0 g | 13.7 g |
| Box capacity/No. | 1000 | 500 |
| Weight/box | 11.0 kg | 7.8 kg |
| Caps/europallet (8 boxes) | 8000 | 4000 |

All measurements and weights are approx. values and do not constitute specification details.

Additional types of metal cans can be supplied on request.

Storage

Store in a dry place, temperature range +5° to +30 °C, for a maximum of 2 years after production date, stacking height: max. 2 pallets

If you have any questions, please contact our technical customer support.

The above information is based on the current state of our knowledge and does not constitute a guarantee for product features. It should not be regarded as any assumption of warranty and no obligations for use can be inferred from it. The use of our product for any purpose other than that specifically recommended by us is at the risk of the user, unless written confirmation was obtained from us as to the suitability of the product for the intended purpose. All information on our products is provided to the best of our knowledge, but owing to the many influences in processing and in the use of our products, we do not assume any liability. In addition, please refer to our general sales and delivery terms for all of our products.